


**POW-R-BLOK™**  
**Single Diode Isolated Module**  
**2000 Amperes / Up to 4000 Volts****Ordering Information:**

Select the complete eight-digit module part number from the table below.

Example: PS414020 is a 4000 Volt, 2000A Average Single Diode Isolated POW-R-BLOK™ Module

Type	Voltage Volts (x100)	Current Amperes (x100)
PS41	36	20
	38	
	40	

**Description:**

Powerex Single Diode Modules are designed for use in applications requiring rectification and isolated packaging. The modules are isolated for easy mounting with other components on a common heatsink.

**Features:**

- Electrically Isolated Heatsinking
- Compression Bonded Elements
- Metal Baseplate
- Low Thermal Impedance for Improved Current Capability

**Benefits:**

- No Additional Insulation Components Required
- Easy Installation
- No Clamping Components Required
- Reduce Engineering Time

**Applications:**

- Bridge Circuits
- AC & DC Motor Drives
- Battery Supplies
- Power Supplies
- Large IGBT Circuit Front Ends

**Absolute Maximum Ratings**

Characteristics	Conditions	Symbol	Units	
Repetitive Peak Reverse Blocking Voltage		$V_{RRM}$	Up to 4000	V
Non-Repetitive Peak Blocking Voltage ( $t < 5$ msec)		$V_{RSM}$	$V_{RRM} + 100V$	V
RMS Current Per Diode (180° Conduction)	180° Conduction, $T_C=89^\circ C$	$I_{F(RMS)}$	3455	A
	<b>180° Conduction, <math>T_C=96^\circ C</math></b>	$I_{F(RMS)}$	<b>3140</b>	A
	180° Conduction, $T_C=103^\circ C$	$I_{F(RMS)}$	2825	A
Average Forward Current Per Diode (180° Conduction)	180° Conduction, $T_C=89^\circ C$	$I_{F(AV)}$	2200	A
	<b>180° Conduction, <math>T_C=96^\circ C</math></b>	$I_{F(AV)}$	<b>2000</b>	A
	180° Conduction, $T_C=103^\circ C$	$I_{F(AV)}$	1800	A
Peak One Cycle Surge Current, Non-Repetitive $T_j = 25C, V_r = 0$	60 Hz	$I_{FSM}$	82,000	A
	50 Hz	$I_{FSM}$	69,800	A
Peak One Cycle Surge Current, Non-Repetitive $T_j = 25C, V_r = V_{rrm}$	60 Hz	$I_{FSM}$	54,750	A
	50 Hz	$I_{FSM}$	46,540	A
Peak One Cycle Surge Current, Non-Repetitive $T_j = 125C, V_r = 0$	60 Hz	$I_{FSM}$	71,400	A
	50 Hz	$I_{FSM}$	60,690	A
Peak One Cycle Surge Current, Non-Repetitive $T_j = 125C, V_r = V_{rrm}$	60 Hz	$I_{FSM}$	47,600	A
	50 Hz	$I_{FSM}$	40,460	A
Peak Three Cycle Surge Current, Non-Repetitive	60 Hz, $T_j = 125C, V_r = V_{rrm}$	$I_{FSM}$	38,220	A
Peak Ten Cycle Surge Current, Non-Repetitive	60 Hz, $T_j = 125C, V_r = V_{rrm}$	$I_{FSM}$	30,020	A
$I^2t$ for Fusing for One Cycle $T_j = 125C, V_r = V_{rrm}$	8.3 milliseconds	$I^2t$	$9.4 \times 10^6$	$A^2 \text{ sec}$
	10 milliseconds	$I^2t$	$8.2 \times 10^6$	$A^2 \text{ sec}$
$I^2t$ for Fusing for One Cycle $T_j = 25C, V_r = 0 V$	8.3 milliseconds	$I^2t$	$28.0 \times 10^6$	$A^2 \text{ sec}$
	10 milliseconds	$I^2t$	$24.4 \times 10^6$	$A^2 \text{ sec}$
Operating Temperature		$T_J$	-40 to +150	°C
Storage Temperature		$T_{sig}$	-40 to +150	°C
Max. Mounting Torque, M6 Mounting Screw			132	in. – Lb.
			15	Nm
Max. Mounting Torque, M10 Terminal Screw			106	in. – Lb.
			12	Nm
Module Weight, Typical			5.33	kg
			11.75	lb
V Isolation @ 25C	60Hz $V_{rms}$ 60 sec	$V_{rms}$	3600	V

Information presented is based upon manufacturers testing and projected capabilities.  
 This information is subject to change without notice.  
 The manufacturer makes no claim as to suitability of use, reliability, capability,  
 or future availability of this product.


**Electrical Characteristics, T<sub>J</sub>=25°C unless otherwise specified**

Characteristics	Symbol	Test Conditions	Min.	Max.	Units
Repetitive Peak Reverse Leakage Current	I <sub>RPM</sub>	Up to 4000V, T <sub>J</sub> =150°C		200	mA
Peak On-State Voltage	V <sub>FM</sub>	I <sub>FM</sub> =3000A, T <sub>J</sub> =150°C		1.20	V
Threshold Voltage, Low-level	V <sub>(TO)1</sub>	T <sub>J</sub> = 150°C, I = 15%I <sub>T(AV)</sub> to πI <sub>T(AV)</sub>		0.701	V
Slope Resistance, Low-level	r <sub>T1</sub>			0.121	mΩ
Threshold Voltage, High-level	V <sub>(TO)2</sub>	T <sub>J</sub> = 150°C, I = πI <sub>T(AV)</sub> to I <sub>TSM</sub>		1.08	V
Slope Resistance, High-level	r <sub>T2</sub>			0.069	mΩ
V <sub>FM</sub> Coefficients, Full Range		T <sub>J</sub> = 150°C, I = 50A to 10kA V <sub>FM</sub> = A+ B Ln I +C I + D Sqrt I	A = B = C = D =	0.383 0.0279 4.56 E-05 6.71 E-03	
Typical Reverse Recovery Time	t <sub>rr</sub>	T <sub>J</sub> = 25°C, I <sub>fm</sub> = 3000A. di/dt = 25 A/us, t <sub>p</sub> = 190 us		25	us


**Thermal Characteristics**

Characteristics	Symbol	Test Conditions	Max.	Units
Thermal Resistance, Junction to Case	R <sub>θJ-C</sub>	Per Module	0.024	°C/W
Thermal Impedance Coefficients	Z <sub>θJ-C</sub>	Z <sub>θJ-C</sub> = K <sub>1</sub> (1-exp(-t/t <sub>1</sub> )) + K <sub>2</sub> (1-exp(-t/t <sub>2</sub> )) + K <sub>3</sub> (1-exp(-t/t <sub>3</sub> )) + K <sub>4</sub> (1-exp(-t/t <sub>4</sub> ))	K <sub>1</sub> = 4.05 E-04 K <sub>2</sub> = 5.19 E-03 K <sub>3</sub> = 1.63 E-02 K <sub>4</sub> = 2.13 E-03	t <sub>1</sub> = 6.24 E-03 t <sub>2</sub> = 2.46 E-01 t <sub>3</sub> = 8.20 t <sub>4</sub> = 35.3
Thermal Resistance, Case to Sink Lubricated	R <sub>θC-S</sub>	Per Module	0.009	°C/W


Typical On-State Forward Voltage Drop  
(T<sub>j</sub> = 150C)




Maximum Transient Thermal Impedance  
(Junction To Case)




Maximum On-State Power Dissipation  
(Sinusoidal Waveform)




Maximum Allowable Case Temperature  
(Sinusoidal Waveform)



Maximum On-State Power Dissipation  
(Rectangular Waveform)



Maximum Allowable Case Temperature  
(Rectangular Waveform)



**POW-R-BLOK™**  
Single Diode Isolated Module  
2000 Amperes / Up to 4000 Volts

DIM.	INCHES	MILLIMETERS
A	7.80	198.1
B	4.00	101.6
C	2.68	68.1
D	6.44	163.6
E	3.44	87.4
F	.28	7.1
G	7.31	185.7
H	7.00	177.8
M	.281	7.1
N	.45	11.4
P	.34	13.7
Q	5.93	150.6
R	.19	4.8
T	.48	12.2
U	2.28	58
V	2.54	64.5
W	4.93	125.2
X	3.81	96.8
Z	2.00	50.8
AA	1.00	25.4
BB	.50	12.7
CC	1.00	25.4
DD	.406	10.3
FF	.66	16.8

