


Powerex, Inc., 200 Hillis Street, Youngwood, Pennsylvania 15697-1800 (412) 925-7272
 Powerex, Europe, S.A. 428 Avenue G. Durand, BP107, 72003 Le Mans, France (43) 41.14.14

General Purpose Rectifier

100-150 Amperes Average
 1600 Volts



R500/R501 (Outline Drawing)



R500/R501 General Purpose Rectifier
 100-150 Amperes Average, 1600 Volts

Ordering Information:

Select the complete part number you desire from the following table:

Type	Voltage		Current		Recovery Time		Recovery Time Circuit		Leads			
	V_{RRM} (Volts)	Code	$I_{F(av)}$ (A)	Code	t_{rr} (μ sec)	Code	Circuit	Code	Case	Code		
R500 (Standard Polarity)	400	04	100	10	7	X	JEDEC	X	DO-8	WA		
	600	06									150	15
	800	08										
	1000	10										
R501 (Reverse Polarity)	1200	12										
	1400	14										
	1600	16										

Example: Type R500 rated at 150A average with $V_{RRM} = 1600V$, and standard flexible lead, order as:

Type	Voltage	Current	Time	Circuit	Leads
R 5 0 0	1 6	1 5	X	X	W A

Features:

- Standard and Reverse Polarities with Color Coded Ceramic Seals
- Flag Lead and Stud Top Terminals Available
- High Surge Current Ratings
- Special Electrical Selection for Parallel and Series Operation
- Compression Bonded Encapsulation

Applications:

- Electromechanical Refining
- Metal Reduction
- General Industrial Rectification



Powerex, Inc., 200 Hillis Street, Youngwood, Pennsylvania 15697-1800 (412) 925-7272
 Powerex, Europe, S.A. 428 Avenue G. Durand, BP107, 72003 Le Mans, France (43) 41.14.14

R500/R501

General Purpose Rectifier

100-150 Amperes Average, 1600 Volts

Absolute Maximum Ratings





Characteristics	Symbol	R500_ _10,	R500_ _15,	Units
		R501_ _10	R501_ _15	
RMS Forward Current	$I_{F(rms)}$	160	236	Amperes
Average Forward Current	$I_{F(av)}$	100	150	Amperes
One-half Cycle Surge Current	I_{FSM}	2300	3000	Amperes
3 Cycle Surge Current	I_{FSM}	1875	2375	Amperes
10 Cycle Surge Current	I_{FSM}	1350	1750	Amperes
I^2t (for Fusing), Times = 8.3 milliseconds	I^2t	22000	37500	A^2sec
Storage Temperature	T_{stg}	-65 to +200	-65 to +200	°C
Operating Temperature	T_j	-65 to +200	-65 to +200	°C
Mounting Torque (Lubricated)		120	120	in-lb

Electrical and Thermal Characteristics

Characteristics	Symbol	Test Conditions	R500_ _10,	R500_ _15,	Units
			R501_ _10	R501_ _15	
Current - Conducting State Maximums					
Forward Voltage Drop	V_{FM}	$T_j = 25^\circ C, I_{FM} = 470A$	1.55	1.40	Volts
Voltage - Blocking State Maximums					
Repetitive Peak Reverse Voltage (Rated Limit)	V_{RRM}		1600	1600	Volts
Non-rep. Trans. Peak Rev. Voltage (Rated Limit)	V_{RSM}	$t_p \leq 5.0msec$	1700	1700	Volts
Reverse Leakage Current	I_{RRM}	T_j at max., $V_{RRM} = \text{Rated}$	30	30	mA
Switching					
Typical Reverse Recovery Time	t_{rr}	$I_{FM} = 314A, t_p = 40\mu sec,$ $di_R/dt = 25A/\mu sec, T_C = 25^\circ C$	7	7	μsec
Thermal					
Maximum Resistance, Junction to Case	$R_{\theta(j-c)}$		0.28	0.28	°C/Watt
Maximum Resistance, Case to Sink (Lubricated)	$R_{\theta(c-s)}$		0.20	0.20	°C/Watt

Powerex, Inc., 200 Hillis Street, Youngwood, Pennsylvania 15697-1800 (412) 925-7272
 Powerex, Europe, S.A. 428 Avenue G. Durand, BP107, 72003 Le Mans, France (43) 41.14.14

R500/R501
General Purpose Rectifier
 100-150 Amperes Average, 1600 Volts



Powerex, Inc., 200 Hillis Street, Youngwood, Pennsylvania 15697-1800 (412) 925-7272
 Powerex, Europe, S.A. 428 Avenue G. Durand, BP107, 72003 Le Mans, France (43) 41.14.14

R500/R501

General Purpose Rectifier

100-150 Amperes Average, 1600 Volts

