

Powerex General Purpose Rectifier Diodes are designed with high locking voltage capability and low forward voltage drop to minimize conduction losses. These are packaged in hermetic, ceramic Pow-R-Disc packages which can be mounted using commercially available clamps and heatsinks or fully assembled to a variety of air or water cooled heat exchangers.

### FEATURES:

- Low On-State Voltage
- Hermetic Ceramic Package
- Excellent Surge and  $I^2t$  Ratings

### APPLICATIONS:

- DC Power Supplies
- Input Rectifiers
- Plating Supplies

### ORDERING INFORMATION

Select the complete 12 digit Part Number using the table below.  
 EXAMPLE: RBS82456XXOO is a 2400V-5680A General Purpose Diode with a typical reverse recovery time of 25 $\mu$ s.

PART	Voltage Rating $V_{DRM}-V_{RRM}$	Voltage Code	Current Rating $I_{TAVG}$	Current Code	Reverse Recovery $t_{RR}$	Lead Code
<b>RBS8</b>	2400	<b>24</b>	5680	<b>56</b>	<b>XX</b>	<b>OO</b>
	2200	<b>22</b>				
	2000	<b>20</b>			25 $\mu$ s typical	
	1800	<b>18</b>				

Revised: 7/28/2005

**Absolute Maximum Ratings**

Characteristic	Symbol	Rating	Units
Repetitive Peak Reverse Voltage	$V_{RRM}$	2400	Volts
Average On-State Current, $T_C=90^\circ\text{C}$	$I_{F(Avg.)}$	5680	A
RMS On-State Current, $T_C=90^\circ\text{C}$	$I_{F(RMS)}$	8922	A
Average On-State Current, $T_C=55^\circ\text{C}$	$I_{F(Avg.)}$	6400	A
RMS On-State Current, $T_C=55^\circ\text{C}$	$I_{F(RMS)}$	10053	A
Peak One Cycle Surge Current, 60Hz, $V_R=0.6*V_{RRM}$	$I_{FSM}$	85,000	A
Fuse Coordination $I^2t$ , 60Hz	$I^2t$	3.01E+07	A <sup>2</sup> s
Peak One Cycle Surge Current, 50Hz, $V_R=0V$	$I_{FSM}$	103,700	A
Fuse Coordination $I^2t$ , 50Hz	$I^2t$	4.48E+07	A <sup>2</sup> s
Operating Temperature	$T_j$	-40 to+175	°C
Storage Temperature	$T_{Stg.}$	-50 to+200	°C
Approximate Weight		2.5	lb
		1.13	Kg
Mounting Force		6,000 - 10,000	lbs
		26.6 - 44.4	Knewtons

Information presented is based upon limited testing or projected capabilities. This information is subject to change without notice. The manufacturer makes no claim as to suitability for use, reliability, capability or future availability of this product.



# RBS8\_\_56XX

## GENERAL PURPOSE RECTIFIER DIODE

Powerex, Inc., 200 Hillis Street, Youngwood, PA 15697-1800 (724)925-7272 PWRX.COM

5680 Amperes 2400 Volts


### Electrical Characteristics, Tj=25°C unless otherwise specified

Characteristic	Symbol	Test Conditions	Rating			Units
			min	typ	max	
Repetitive Peak Reverse Leakage Current	$I_{RRM}$	Tj=175°C, $V_{RRM}$ =Rated		100	150	ma
Peak On-State Voltage	$V_{FM}$	Tj=175°C, $I_{FM}$ =4000A			0.95	V
$V_{FM}$ Model, Low Level	$V_0$	Tj=175°C			0.661	V
$V_{FM} = V_0 + r \cdot I_{FM}$	r	15% $I_{FM} - \pi \cdot I_{FM}$			6.59E-05	$\Omega$
$V_{FM}$ Model, High Level	$V_0$	Tj=175°C			0.799	V
$V_{FM} = V_0 + r \cdot I_{FM}$	r	$\pi \cdot I_{FM} - I_{FSM}$			5.64E-05	$\Omega$
$V_{FM}$ Model, 4-Term	A	Tj=175°C			0.613	
$V_{FM} = A + B \cdot \ln(I_{FM}) +$	B	15% $I_{FM} - I_{FSM}$			-0.0118	
$C \cdot (I_{FM}) + D \cdot (I_{FM})^{1/2}$	C				3.926E-05	
	D				0.004637	
Reverse Recovery Time	$t_{RR}$	Tj=25°C, $I_{FM}$ =400A $di_R/dt = 25 A/\mu s$		25		$\mu s$


### Thermal Characteristics

Characteristic	Symbol	Test Conditions	Rating			Units	
			min	typ	max		
Thermal Resistance							
Junction to Case	$R\theta_{jc}$	Double side cooled		0.0085	0.0095	°C/Watt	
Case to Sink	$R\theta_{cs}$	Double side cooled		0.0015	0.002	°C/Watt	
Thermal Impedance Model	$Z\theta_{jc}$	Double side cooled					
$Z\theta_{jc}(t) = \sum(A(N) \cdot (1 - \exp(-t/\text{Tau}(N))))$ where:							
			N =	1	2	3	4
			A(N) =	5.224E-05	1.186E-03	2.905E-03	5.351E-03
			Tau(N) =	2.648E-06	3.427E-02	2.736E-01	2.030E+00

**Maximum On-State Voltage Drop**




**MAXIMUM TRANSIENT THERMAL IMPEDANCE**




**Maximum On-State Power Dissipation**

SINE WAVE




**Maximum Allowable Case Temperature**

SINE WAVE



**Maximum On-State Power Dissipation**

SQUARE WAVE



**Maximum Allowable Case Temperature**

SQUARE WAVE

