

The T9S0 SCR employs a Center-Fired amplifying gate structure which allows the SCR to be reliably operated at high di/dt and high dv/dt conditions in phase control applications.

**FEATURES:**

- Low On-State Voltage
- High di/dt Capability
- High dv/dt Capability
- Hermetic Ceramic Package
- Excellent Surge and I<sup>2</sup>t Ratings

**APPLICATIONS:**

- DC Power Supplies
- Plating Supplies
- Welding Supplies

**ORDERING INFORMATION**

Select the complete 12 digit Part Number using the table below.  
EXAMPLE: **T9S0182003DH** is an 1800V-1500A SCR with 200ma IGT and 12 inch gate and cathode potential leads.

PART	Voltage Rating V <sub>DRM</sub> -V <sub>RRM</sub>	Voltage Code	Current Rating I <sub>tavg</sub>	Current Code	Turn-Off T <sub>q</sub>	Gate I <sub>GT</sub>	Leads
<b>T9S0</b>	1200V	<b>12</b>	2000A	<b>20</b>	<b>0</b>	<b>3</b>	<b>DH</b>
	1400V	<b>14</b>					
	1600V	<b>16</b>			400us typ.	200ma	12"
	1800V	<b>18</b>					

Revised: 5/5/2008

**Absolute Maximum Ratings**

Characteristic	Symbol	Rating	Units
Repetitive Peak Voltage	$V_{DRM}-V_{RRM}$	1800	Volts
Average On-State Current, $T_C=72^\circ\text{C}$	$I_{T(Avg.)}$	2000	A
RMS On-State Current, $T_C=72^\circ\text{C}$	$I_{T(RMS)}$	3142	A
Average On-State Current, $T_C=55^\circ\text{C}$	$I_{T(Avg.)}$	2200	A
RMS On-State Current, $T_C=55^\circ\text{C}$	$I_{T(RMS)}$	3456	A
Peak One Cycle Surge Current, 60Hz, $V_R=0V$	$I_{TSM}$	27,000	A
Peak One Cycle Surge Current, 50Hz, $V_R=0V$	$I_{TSM}$	25,456	A
Fuse Coordination $I^2t$ , 60Hz	$I^2t$	3.04E+06	A <sup>2</sup> s
Fuse Coordination $I^2t$ , 50Hz	$I^2t$	3.24E+06	A <sup>2</sup> s
Critical Rate-of-Rise of On-State Current Repetitive	di/dt	100	A/us
Critical Rate-of-Rise of On-State Current Non-Repetitive	di/dt	200	A/us
Critical Rate-of-Rise of Off-State Voltage $V_D = \frac{1}{2} \cdot V_{DRM}$	dv/dt	1000	V/us
Peak Gate Power, 100us	$P_{GM}$	16	Watts
Average Gate Power	$P_{G(avg)}$	5	Watts
Operating Temperature	$T_j$	-20 to +125	°C
Storage Temperature	$T_{Stg.}$	-50 to +150	°C
Approximate Weight		0.65	lb
		0.29	Kg
Mounting Force		5500-6000	lbs
		24.5 - 26.7	Knewtons

Information presented is based upon limited testing or projected capabilities. This information is subject to change without notice. The manufacturer makes no claim as to suitability for use, reliability, capability or future availability of this product.


**Electrical Characteristics, Tj=25°C unless otherwise specified**

Characteristic	Symbol	Test Conditions	Rating			Units
			min	typ	max	
Repetitive Peak Leakage Current	$I_{DRM}/I_{RRM}$	Tj=125°C, $V_{DRM}$ =Rated			150	ma
Peak On-State Voltage	$V_{TM}$	Tj=125°C, $I_{TM}$ =1500A			1.15	V
$V_{TM}$ Model, Low Level	$V_0$	Tj=125°C			0.755	V
	$V_{TM} = V_0 + r \cdot I_{TM}$	$15\% I_{TM} - \pi \cdot I_{TM}$			2.26E-01	mΩ
$V_{TM}$ Model, High Level	$V_0$	Tj=125°C			1.044	V
	$V_{TM} = V_0 + r \cdot I_{TM}$	$\pi \cdot I_{TM} - I_{TSM}$			1.50E-01	mΩ
$V_{TM}$ Model, Hiç 4-Term	A	Tj=125°C			0.200	
	$V_{TM} = A + B \cdot \ln(I_{TM}) +$	$15\% I_{TM} - I_{TSM}$			0.083	
	$C \cdot (I_{TM}) + D \cdot (I_{TM})^{1/2}$				1.28E-04	
					3.27E-03	
Turn-On Delay Time	$t_d$	$V_D = 0.5 \cdot V_{DRM}$ Gate Drive: 40V - 20Ω		1.5		us
Turn-Off Time	$t_q$	Tj=125°C $dv/dt = 20V/us$ to 80% $V_{DRM}$		400		us
Gate Trigger Current	$I_{GT}$	Tj=25°C $V_D = 12V$	30	90	200	ma
Gate Trigger Voltage	$V_{GT}$		0.6	1.6	3.0	V
Peak Reverse Gate Voltage	$V_{GRM}$				5	V


**Thermal Characteristics**

Characteristic	Symbol	Test Conditions	Rating			
			max			Units
Thermal Resistance						
Junction to Case	$R\theta_{jc}$	Double side cooled			0.015	°C/Watt
Case to Sink	$R\theta_{cs}$	Double side cooled			0.0025	°C/Watt
Thermal Impedance Model						
	$Z\theta_{jc}$	Double side cooled				
$Z\theta_{jc}(t) = \sum(A(N) \cdot (1 - \exp(-t/\tau(N))))$						
where: N = 1      2      3      4						
$A(N) = 1.42E-03 \quad 2.97E-03 \quad 6.07E-03 \quad 4.50E-03$						
$\tau(N) = 5.95E-05 \quad 2.76E-02 \quad 4.01E-01 \quad 2.00E+00$						


### Maximum On-State Voltage Drop



### MAXIMUM TRANSIENT THERMAL IMPEDANCE



## Maximum On-State Power Dissipation




## Maximum Allowable Case Temperature



## Maximum On-State Power Dissipation

Square Waveform



## Maximum Allowable Case Temperature

Square Waveform

